





2GR-FE LUBRICATION

SST

	09032-00100	Oil Pan Seal Cutter	-
	09228-06501	Oil Filter Wrench	-
	09316-60011	Transmission & Transfer Bearing Replacer	-
	(09316-00011)	Replacer Pipe	-

RECOMMENDED TOOLS

	09200-00010	Engine Adjust Kit	-
---	-------------	-------------------	---

EQUIPMENT

Container	-
Deep socket wrench (24 mm)	-
Hose	Oil filter
Oil pressure gauge	-
Socket wrench (27 mm)	-
Straightedge	-
Torque wrench	-
Wooden block	-

LUBRICANT

Item		Capacity	Classification
Oil grade		-	ILSAC multigrade engine oil is recommended. SAE 5W-30 is the best choice for good fuel economy and good starting in cold weather.
Drain and refill	With oil filter change	6.1 liters (6.4 US qts, 5.4 Imp. qts)	-
	Without oil filter change	5.7 liters (6.0 US qts, 5.0 Imp. qts)	-
Dry fill		6.5 liters (6.9 US qts, 5.7 Imp. qts)	-

PP

SSM

Toyota Genuine Adhesive 1344, Three Bond 1344 or Equivalent	-
Toyota Genuine Seal Packing Block, Three Bond 1207B or Equivalent	-
Toyota Genuine Seal Packing 1282B, Three Bond 1282B or Equivalent	-